

數位式噪音箱

(附專業分析軟體)



[Http://www.umarket.com.tw](http://www.umarket.com.tw)

數位式噪音計

規格：

UM 321 Sound Level Meter

- ☒ **RS-232 Interface**
- ☒ **Bar Graph Indication**
- ☒ **MAX/MIN Function**
- ☒ **Auto Ranging(30~130dB)**
- ☒ **Resolution 0.1dB**
- ☒ **Clock Display**
- ☒ **Level Range Display**
- AC/DC Signal Output**

Microphone:

Electorate condenser microphone

Accuracy:

±1.5 dB (ref 94dB @1KHz)

Level Range:

Lo = 30 ~ 80 dB

Med = 50 ~ 100 dB

Hi = 80 ~ 130 dB

Auto=30~130 dB

Frequency Weighting:

A , C

Time Weighting:

Fast , Slow

Auxiliary Outputs:

AC output

Output voltage: 1Vrms (at full scale)

Output impedance: Approx:600Ω

AC output

Output voltage: 10mV / dB

Output impedance: Approx:50Ω

Dynamic Range:

50 dB

Frequency Range:

31.5Hz to 8KHz

Battery Type:

9V Battery

Battery Life:

50 hours (with alkaline battery)

Operation Temp.:

0°C~ 40°C(<80% R.H.) 9V Battery, Carrying Case, Calibration

Screwdriver, Windscreen

Accessories:

Battery, Operation Manual, Carrying Case, Calibration Screwdriver, Windscreen, 3.5Φ plug