

## EX9520 RS485 MODULE



### Key Specifications/Special Features:

- Input: RS-232 protocol
- Speed: "AutoPro" designed auto switch baud rate, 300~115200Bps
- 256 modules max. in one RS-485 network without repeater
- 3000V isolation
- Multiple baud rate; multiple data format
- Communication distance:
  - o 2.1km/9600Bs
  - o 2.7km/4800Bps
  - o 3.6km/2400Bps
  - o Power requirements: +10V-30VDC
  - o Power consumption 2.2W(max.)
  - o Dimensions: 7 x 10 x 2cm
  - o Series products: RS422/RS485/RS232; digital I/O AD/DA module
  - o Operation Temp: -25°C to +75°C
  - o Storage Temp: -40°C to +80°C

|                  | 422 | 485 | Isolate(PLC) | Repeater |
|------------------|-----|-----|--------------|----------|
| EX9520           |     | ✓   |              |          |
| EX9520R          |     | ✓   | ✓            |          |
| EX9520A          | ✓   | ✓   |              |          |
| EX9520AR         | ✓   | ✓   | ✓            |          |
| EX9510           |     | ✓   |              | ✓        |
| EX9510A          | ✓   | ✓   |              | ✓        |
| EX9520 (ISA/PCI) |     | ✓   |              |          |
| EX9520A(ISA/PCI) | ✓   | ✓   |              |          |

達因國際實業有限公司 (Union Market.Com)

T:+886-2-27925208

F:+886-2-27916140

[Http://www.umarket.com.tw](http://www.umarket.com.tw)