



FEATURE

- Auto range.
- PC interface.
- LED back light.
- Four channel input.
- Four channel display.
- Resolution 0.1°C/0.1°F
- With windows software.
- Auto shut off for battery saving.
- 16,000 records data logger each channel.
- Isolated input protection up to 250 Vac between any two inputs.

Four Channel Display



T1-T2 Display



SPECIFICATIONS

Measurement Range: -200°C~1372°C (K type)
-328°F~2501°F (K type)

Accuracy: -200°C~1372°C.....± 0.1%rdg+0.7°C
-328°F~2501°F.....± 0.1%rdg+1.4°F

Battery Type: 9V Battery

Operating Condition: -10°C to 50°C (<90%RH)

Storage Condition: -40°C to 60°C(<75%RH)

Dimensions: 197mm × 65mm × 36mm

Weight: Approx.310g

Accessories: Battery, Operation Manual, Carrying Case
Temperature Probe TP-K01 × 2Pcs
USB Cable, Software.



LED Back Light

* The specifications and other information in this catalogue are subject to change without prior notice.

UNION Market Enterprise Company LTD.
1F., No.2, Alley 6, Lane 423, Zhuangjing Rd.,
Xinyi District, Taipei City 110, Taiwan
TEL: 02-27221198 E-Mail : service@umarket.com
FAX: 02-27221120 http : //www.umarket.com.tw

Distributed by: