

26.600 -

 -

 -

 -

 -

Input	[bar]																		
	1,0	1	0	0	1														
absolute pressure	1,6	1	6	0	1														
special version 500	2,5	2	5	0	1														
	4,0	4	0	0	1														
	6,0	6	0	0	1														
	10	1	0	0	2														
	16	1	6	0	2														
	25	2	5	0	2														
	40	4	0	0	2														
	60	6	0	0	2														
	100	1	0	0	3														
	160	1	6	0	3														
	250	2	5	0	3														
	400	4	0	0	3														
	-1 ... 0 ¹	X	1	0	2														
customer		X	X	X	X														
Output																			
4 ... 20 mA / 2-wire						1													
0 ... 10 V / 3-wire						3													
Electrical Connection																			
Male and female plug DIN 43650							1	0	0										
Cable gland incl. Cable ²							4	0	0										
customer							X	X	X										
Mechanical Connection																			
G1/4" DIN 3852								3	0	0									
customer								X	X	X									
Special version																			
standard												0	0	0					
oxygen application												0	0	7					
absolute pressure												5	0	0					
customer												X	X	X					

¹ The accuracy in this pressure range is 1 % FSO

¹ different cable types and lengths deliverable, standard: 2 m PVC cable (without ventilation tube), optionally cable with ventilation tube